


Precast elastic tiles, monolayer system, made of recycled black rubber granules, pigments and polyurethane resins. Analysed and manufactured according to the EN-1177 European standard, thus ensuring that this product has an impact absorption over 70%.

Ref.	A	B	H	
JBA20M	500	500	20	700
JBA40M	500	500	40	1300
JBA60M	1000	500	60	1680
JBA80M	1000	500	80	2000

[Certificate](#) | [Catalogue](#) | [HD image](#)

The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

Materials:

Use: security areas around playground equipments for children.

Installation: without maintenance, easy and quick installation. A clean and solid hard concrete or asphalt foundation is recommended to carry out this process.

Optional: other colours and thicknesses.

Discolouration can happen with time without affecting the characteristics of the tile.

Maintenance:

Once a year according to the use of the playground areas and weather conditions. Maintenance includes the cleaning and checking of the surface. Damaged tiles must be replaced. In case of depigmentation, a resin primer must be applied to protect the ground.

An annual examination of the coating absorption levels of each equipment installed on the area is recommended to ensure they comply with the EN-1177 standard.

Note: colours are approximations of the original colours.


Tolerance +- 2%

Ground anchoring screws not included.

Alternatives:



[JBC01](#)



[JBS](#)

Projects:

